

**The MaxiCharger is a wall-mounted single-outlet, universal Type 2 socket EV charger. It is available in both online and offline models. It is OCPP 1.6 compliant, has dynamic load balancing built in and has PME fault detection incorporated.**

It is available in three attractive finishes: silver, black or white. The MaxiCharger is robust, aesthetically pleasing and suitable for all environments. It charges up to 7.4 kW on a single-phase connection and 11 kW/22 kW on a three-phase connection.



### Technical Specification

Charging type	Mode 3, Type 2
Charging power	7.4 kW/11 kW/22 kW
Rated current	32 A/16 A
Rated frequency	50 Hz
Input/output voltage	400 V±15%, 3P+N+PE/230 V±15%, 1P+N+PE
Network type	TT, TN
RCB	Internal RCD Type A protection included
Protection	Overcurrent, overvoltage, undervoltage, ground fault including DC residual current protection (DC Leakage), integrated surge protection
PME fault detection	Incorporated within the unit

### User Interface

Status indication	LED/APP
User interface	MaxiCharger APP, MaxiCharger Service Software, web portal
Connectivity	4G, Bluetooth, Wi-Fi, Ethernet
Communication protocols	OCPP 1.6
User authentication	APP, RFID card, QR code

Find out more on the next page →



### General Characteristics

IP and IK rating	IP65, IK08
Operating altitude	2000 m
Operating temperature range	-40°C ~ + 55°C
Storage temperature range	-40°C ~ + 85°C
Mounting	Wall or floor using a pedestal
Weight	Three-phase socket: 3920 g Single-phase socket: 3600 g
Dimensions HxWxD	336 × 187 × 85 mm

### Software Update

Software update	APP or web portal
-----------------	-------------------

### Certification and Standards

Safety standards	EN/IEC 61851-1, EN/IEC 62196-2, EN/IEC 62955
Certification	CE, TUV
Warranty	36 months