

MaxiCharger Pillar with LCD Screen

Three-Phase Datasheet

The MaxiCharger with LCD Screen three-phase EV charging point offers 11/22kW fast charging via its universal Type 2 socket. This smart EV charging point is complete with a 5-inch LCD touchscreen, enabling drivers to understand real-time EV charging behaviour and data, as well as providing businesses with the opportunity to utilise the screen for advertising purposes.

With built-in PME fault detection, static load management capabilities, as well as smart functionalities, the MaxiCharger with LCD screen EV charging point provides a feature-rich solution for commercial requirements.



Product Code	Product Name and Description
EVAUTCS4GLCD	MaxiCharger 3 Phase 4G AC Wallbox with LCD Screen 11kW/22kW Socket
EVMCSPP	MaxiCharger Single Project Pillar Housing
EVMCDPP	MaxiCharger Dual Project Pillar Housing

Please note that if opting for a dual MaxiCharger Pillar, x2 MaxiChargers are required. The same principle applies to 3-way and 4-way options.

Technical Specification	
Charging type	Mode 3, Type 2
Charging power	11 kW/22 kW on three-phase
Rated current	32 A/16 A
Rated frequency	50 Hz
Input/output voltage	400 V+-15%: L1, L2, L3, N, PE
Network type	TT, TN
RCD	Integrated 6mA DC + 30mA AC leakage detection
Protection	Overcurrent, overvoltage, undervoltage, ground fault including DC residual current protection, integrated surge protection
PME fault detection	Incorporated within the unit
MID Meter	Internally built-in

For more information, call 0330 058 7144 or email customerservice@sevadis.com View our full range of EV chargers online www.sevadis.com



MaxiCharger Pillar with LCD Screen

Three-Phase Datasheet



User Interface	
Status indication	LED/APP
User interface	MaxiCharger APP, MaxiCharger Service Software, web portal
Connectivity	Bluetooth, Wi-Fi, Ethernet, 4G (SIM not included)
Communication protocols	OCPP 1.6J
User authentification	APP, RFID card, QR code

General Characteristics	
IP and IK rating	IP54, IK08
Operating altitude	2000 m
Operating temperature range	-40°C ~ + 55°C
Storage temperature range	-40°C ~ + 85°C
Weight	3920 g
Dimensions (WxHxD)	Unit: 187 mm x 336 mm × 85 mm Pillar: 362 mm x 1197 mm x 270 mm

Software Update	
Software update	APP or web portal

Certification and Standards	
Safety standards	EN/IEC 61851-1, EN/IEC 62196-2, EN/IEC 62955, BS7671
Certification	CE, UKCA (TUV) Compliant to the Electric Vehicles (Smart Charge Points) Regulations 2021, inc. Schedule 1
Warranty	36 months

For more information, call 0330 058 7144 or email customerservice@sevadis.com View our full range of EV chargers online www.sevadis.com