

MaxiCharger Pillar Three-Phase Datasheet

FOR BUILT ENVIRONMENT PROJECTS

The MaxiCharger Pillar is a floor-standing, smart, universal Type 2 socket EV charger that is available in single and dual-socket options. It is OCPP 1.6J compliant, has built-in PME fault detection on single and three-phase connection, and both static load management and dynamic load balancing capabilities.

Allowing EV drivers to charge with 11 kW or 22 kW charging speeds, the MaxiCharger is an ideal charging solution for commercial charging requirements. The pillar housing is finished in a powder-coated steel with bespoke branding options available.



Product Code	Product Name and Description	
EVMX224G	MaxiCharger 3 Phase Smart 4G AC Wallbox 11 kW/22 kW Socket	
EVMX22LCD4G	MaxiCharger 3 Phase Smart 4G AC Wallbox With LCD Screen 11 kW/22 kW Socket	
EVMCSPP	MaxiCharger Single Pedestal Housing	
EVMCDPP	MaxiCharger Dual Pedestal Housing	
Please note that if opting for a dual MaxiCharger Pillar, x2 MaxiChargers are required. The same principle applies to 3-way and 4-way options.		

Technical Specification	
Charging type	Mode 3, Type 2
Charging power	11 kW/22 kW on three-phase
Rated current	32 A/16 A
Rated frequency	50 Hz
Input/output voltage	400 V+-15%: L1, L2, L3, N, PE
Network type	TT, TN
RCD	Integrated 6mA DC + 30mA AC leakage detection
Protection	Overcurrent, overvoltage, undervoltage, ground fault including DC residual current protection, integrated surge protection
PME fault detection	Incorporated within the unit



MaxiCharger Pillar Three-Phase Datasheet





User Interface	
Status indication	LED/APP
User interface	MaxiCharger APP, MaxiCharger Service Software, web portal
Connectivity	Bluetooth, Wi-Fi, Ethernet, 4G
Communication protocols	OCPP 1.6J
User authentification	APP, RFID card, QR code

General Characteristics	
IP and IK rating	IP54, IK08
Operating altitude	2000 m
Operating temperature range	-40°C ~ + 55°C
Storage temperature range	-40°C ~ + 85°C
Weight	3920 g
Dimensions (WxHxD)	Unit: 187 mm x 336 mm × 85 mm Pillar: 362 mm x 1197 mm x 270 mm

Software Update Software update APP or web portal

Certification and Standards	
Safety standards	EN/IEC 61851-1, EN/IEC 62196-2, EN/IEC 62955, BS7671
Certification	CE, UKCA (TUV) Compliant to the Electric Vehicles (Smart Charge Points) Regulations 2021, inc. Schedule 1
Warranty	36 months